



# Wire and Cable Marking

CONTINUED

PORTABLE PRINTING AND LABELS

WIRE & CABLE MARKING TLS2200 / TLS PC LINK LABELS

## ▶ PERMASLEEVE™ WIRE MARKING SLEEVES



### Heat-Shrinkable White Polyolefin (B-342)

Part Number	Sleeves Per Roll	Sleeve Dimensions		Range of Wire Dia.		Approx. Wire Gauge*	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A Inch (mm)	B Inch (mm)	Min Inch (mm)	Max Inch (mm)		2	7	10	2	7	10
<b>1.015" Marker Width</b>												
<b>WHITE 3:1 SHRINK RATIO</b>												
PSPT-094-1-WT	100	1.015 (25.78)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	22	0	0	1	0	0
BPSPT-094-1-WT	2500	1.015 (25.78)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	22	0	0	1	0	0
PSPT-125-1-WT	100	1.015 (25.78)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	22	0	0	1	0	0
BPSPT-125-1-WT	1000	1.015 (25.78)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	22	0	0	1	0	0
PSPT-187-1-WT	100	1.015 (25.78)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	22	9	0	2	1	0
BPSPT-187-1-WT	1000	1.015 (25.78)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	22	9	0	2	1	0
PSPT-250-1-WT	100	1.015 (25.78)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	22	9	6	3	1	1
BPSPT-250-1-WT	1000	1.015 (25.78)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	22	9	6	3	1	1
PSPT-375-1-WT	100	1.015 (25.78)	0.645 (16.38)	0.125 (3.18)	0.320 (8.13)	12-6	22	9	6	5	2	1
PSPT-500-1-WT	100	1.015 (25.78)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	22	9	6	7	3	2
BPSPT-500-1-WT	100	1.015 (25.78)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	22	9	6	7	3	2
PSPT-1000-1-WT	50	1.015 (25.78)	1.660 (42.16)	0.450 (11.43)	0.950 (24.13)	1-500	22	9	6	16	8	5
<b>YELLOW 3:1 SHRINK RATIO</b>												
PSPT-094-1-YL	100	1.015 (25.78)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	22	0	0	1	0	0
PSPT-125-1-YL	100	1.015 (25.78)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	22	0	0	1	0	0
PSPT-187-1-YL	100	1.015 (25.78)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	22	9	0	2	1	0
PSPT-250-1-YL	100	1.015 (25.78)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	22	9	6	3	1	1
PSPT-375-1-YL	100	1.015 (25.78)	0.645 (16.38)	0.125 (3.18)	0.320 (8.13)	12-6	22	9	6	5	2	1
PSPT-500-1-YL	100	1.015 (25.78)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	22	9	6	7	3	2
PSPT-1000-1-YL	50	1.015 (25.78)	1.660 (42.16)	0.450 (11.43)	0.950 (24.13)	1-500	22	9	6	16	8	5
<b>1.765" Marker Width</b>												
<b>WHITE 3:1 SHRINK RATIO</b>												
PSPT-094-175-WT	100	1.765 (44.83)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	41	0	0	1	0	0
BPSPT-094-175-WT	2500	1.765 (44.83)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	41	0	0	1	0	0
PSPT-125-175-WT	100	1.765 (44.83)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	41	0	0	1	0	0
BPSPT-125-175-WT	1000	1.765 (44.83)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	41	0	0	1	0	0
PSPT-187-175-WT	100	1.765 (44.83)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	41	17	11	3	1	1
BPSPT-187-175-WT	1000	1.765 (44.83)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	41	17	11	3	1	1
PSPT-250-175-WT	100	1.765 (44.83)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	41	17	11	3	1	1
BPSPT-250-175-WT	1000	1.765 (44.83)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	41	17	11	3	1	1
PSPT-375-175-WT	100	1.765 (44.83)	0.645 (16.38)	0.125 (3.18)	0.320 (8.13)	12-6	41	17	11	5	2	1
BPSPT-375-175-WT	1000	1.765 (44.83)	0.645 (16.38)	0.125 (3.18)	0.320 (8.13)	12-6	41	17	11	5	2	1
PSPT-500-175-WT	100	1.765 (44.83)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	41	17	11	7	3	2
BPSPT-500-175-WT	1000	1.765 (44.83)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	41	17	11	7	3	2
PSPT-1000-175-WT	50	1.765 (44.83)	1.660 (42.16)	0.450 (11.43)	0.950 (24.13)	1-500	41	17	11	16	8	5
BPSPT-1000-175-WT	500	1.765 (44.83)	1.660 (42.16)	0.450 (11.43)	0.950 (24.13)	1-500	41	17	11	16	8	5
<b>YELLOW 3:1 SHRINK RATIO</b>												
PSPT-094-175-YL	100	1.765 (44.83)	0.182 (4.62)	0.023 (0.58)	0.080 (2.03)	28-18	41	0	0	1	0	0
PSPT-125-175-YL	100	1.765 (44.83)	0.235 (5.96)	0.046 (1.17)	0.110 (2.79)	22-16	41	0	0	1	0	0
PSPT-187-175-YL	100	1.765 (44.83)	0.335 (8.50)	0.062 (1.57)	0.150 (3.81)	18-12	41	17	11	3	1	1
PSPT-250-175-YL	100	1.765 (44.83)	0.439 (11.15)	0.094 (2.39)	0.215 (5.46)	16-10	41	17	11	3	1	1
PSPT-375-175-YL	100	1.765 (44.83)	0.645 (16.38)	0.125 (3.18)	0.320 (8.13)	12-6	41	17	11	5	2	1
PSPT-500-175-YL	100	1.765 (44.83)	0.851 (21.61)	0.187 (4.75)	0.450 (11.43)	8-1	41	17	11	7	3	2
PSPT-1000-175-YL	50	1.765 (44.83)	1.660 (42.16)	0.450 (11.43)	0.950 (24.13)	1-500	41	17	11	16	8	5

\* Based on National Electric Code insulation measurement of THHN Wire.


**Note:** Labels are sorted in order by width, height, 3 digit material number (within part number), then die number (within part number).

# Wire and Cable Marking

CONTINUED

## BRADYSLEEVE™ WIRE MARKING SLEEVES

Heat-Shrinkable White Polyolefin (B-321)



Part Number	Sleeves Per Roll	Sleeve Dimensions		Range of Wire Dia.		Approx. Wire Gauge*	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A Inch (mm)	B Inch (mm)	Inch (mm) Min	Inch (mm) Max		2	7	10	2	7	10
<b>0.450" Sleeve Width</b>												
PTS-0.45-350-321	500	0.450 (11.43)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	9	3	0	2	1	0
PTS-0.45-500-321	500	0.450 (11.43)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	9	3	2	4	2	1
<b>0.950" Sleeve Width</b>												
PTS-0.95-350-321	500	0.950 (24.13)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	21	9	0	2	1	0
PTS-0.95-500-321	500	0.950 (24.13)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	21	9	6	4	2	1
PTS-0.95-750-321	250	0.950 (24.13)	0.750 (19.05)	0.335 (8.51)	0.390 (9.91)	2-4	21	9	6	7	3	2
PTS-0.95-1000-321	250	0.950 (24.13)	1.000 (25.40)	0.375 (9.53)	0.540 (13.72)	00-1	21	9	6	10	5	3
<b>1.900" Sleeve Width</b>												
PTS-1.90-350-321	500	1.900 (48.26)	0.350 (8.89)	0.075 (1.91)	0.160 (4.06)	10-16	44	18	0	2	1	0
PTS-1.90-500-321	500	1.900 (48.26)	0.500 (12.70)	0.160 (4.06)	0.235 (5.97)	8-10	44	18	12	4	2	1
PTS-1.90-750-321	250	1.900 (48.26)	0.750 (19.05)	0.335 (8.51)	0.390 (9.91)	2-4	44	18	12	7	3	2
PTS-1.90-1000-321	250	1.900 (48.26)	1.000 (25.40)	0.375 (9.53)	0.540 (13.72)	00-1	44	18	12	10	5	3

\* Based on National Electric Code insulation measurement of THHN Wire.

**Note:** Labels are sorted in order by width, height, 3 digit material number (within part number), then die number (within part number).

## BRADY TAGS® PRINTABLE TAGS

Polyethylene (B-109)




Diagram	Part Number	Tags Per Roll	Tag Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:			Applications/Description
			Inch (mm) A	Inch (mm) B	2	7	10	2	7	10	
▲	PTL-12-109	100	0.750 (19.05)	3.000 (76.20)	45	19	12	6	3	2	Product ID for harsh environments/tear resistant
▲	BPTL-12-109	1000	0.750 (19.05)	3.000 (76.20)	45	19	12	6	3	2	Product ID for harsh environments/tear resistant
▶	PTL-36-109	250	1.750 (44.45)	1.125 (28.57)	34	14	9	12	6	4	Product ID for harsh environments/tear resistant


## ELECTRICAL COMPONENT MARKERS

Polypropylene (B-412)

Part Number	Labels Per Roll	Label Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		Inch (mm) A	Inch (mm) B	2	7	10	2	7	10
PTL-57-412	50 ft (15.24 m)	0.500 (12.70)	continuous	50	50	50	5	2	1

## TERMINAL BLOCK MARKERS

Repositional Vinyl Cloth (B-498)



Part Number	Roll Length Ft. (m)	Label Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A Inch (mm)	B Ft. (m)	2	7	10	2	7	10
PTLTB-498-240	30 ft (9.10 m)	0.240 (6.09)	30 ft (9.10 m)	5	2	1	—	N/A	—
BPTLTB-498-240	300 ft (91.44 m)	0.240 (6.09)	300 ft (91.44 m)	5	2	1	—	N/A	—
PTLTB-498-318	30 ft (9.10 m)	0.318 (8.07)	30 ft (9.10 m)	7	3	2	—	N/A	—
BPTLTB-498-318	300 ft (91.44 m)	0.318 (8.07)	300 ft (91.44 m)	7	3	2	—	N/A	—
PTLTB-498-375	30 ft (9.10 m)	0.375 (9.52)	30 ft (9.10 m)	8	3	2	—	N/A	—
BPTLTB-498-375	300 ft (91.44 m)	0.375 (9.52)	300 ft (91.44 m)	8	3	2	—	N/A	—

PORTABLE PRINTERS AND LABELS

WIRE AND CABLE MARKING

TLS2200 / TLS PC LINK LABELS