

Sleeve and Datab™ Printer

The SLV-DAT-PTR 24 pin printer is designed to print on all Brady pin-fed products. Using your computer and LabelMark™ software, you can utilize BradySleeve™, PermaSleeve™, DuraSleeve™ and Datab™ materials.

PRODUCT GUIDE

Specification/ Characteristic	Detail
Model	Lexmark 2390 Plus (Modified)
Technology	Dot Matrix
Speed at 10 cpi	233 cps (fast draft) 210 cps (draft) 70 cps (near letter quality)
Speed at 12 cpi	252 cps (fast draft) 252 cps (draft) 84 cps (near letter quality)
Memory	32KB
Network Support	Lexmark external print servers
Compatibility	IBM PPS II 2390/91; Proprinter 24P 24E, XL24E; Execjet, Epson, LQ-850; LQ-1050; IBM PS/1 printer
Print Quality	Letter quality Near letter quality 360 x 360 dpi graphics
Font Selection	8 resident 7 resident bar codes
Maximum Print Width	8" (203.2mm)
Paper Handling	Virtually straight paper path; friction feed; movable push/pull tractors; four bottom/front paper feeds; auto-load assist
Usability Features	One-touch control panel; panel-selectable forms macros; easy front loading; quiet mode; variable forms-length settings
Environmental Features	Complies with the EPA's Energy Star program for low power consumption
Size/Weight	7.5" H x 19.6" W x 11.3" D; 14.8 lbs.
Acoustics	55 decibels running 53.3 decibels in quiet mode (51 decibels with acoustic option)
Supplies	Provided with a series R5000 ribbon (R5390) re-inking ribbon. Also available is a series R2000 ribbon (R2080) non-re-inking ribbon (recommended for B-619 and B-969 materials)
Duty Cycle	25% average usage: 500,000 char/month

Part Number	Description
SLV-DAT-PTR	Sleeve and Datab Printer



The SLV-DAT-PTR is ideal for printing on all pin-fed materials.