


# General and Industrial Identification Labels

CONTINUED

PORTABLE PRINTING AND LABELS

GENERAL & INDUSTRIAL ID TLS2200 / TLS PC LINK LABELS




## ▶ RATING / NAMEPLATE LABELS CONTINUED

**Permanent Glossy Polyester (B-422, B-423, B-459), General Purpose White Paper (B-424), Flexible Vinyl (B-427), Permanent Metallized Polyester (B-428, B-435), Ultra-Aggressive Glossy Polyester (B-483), Ultra-Aggressive Matte Metallized Polyester (B-486), Matte Polyester (B-488), Ultra-Aggressive Matte Polyester (B-489), Nylon Cloth (B-499)**

Surface Suitability	Diagram	Part Number	Labels Per Roll	Label Dimensions		Applications/Description	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
				A Inch (mm)	B Inch (mm)		2	7	10	2	7	10
◆	▲	PTL-38-424	100	4.000 (101.60)	1.900 (48.26)	General identification and Asset ID	50	41	30	20	10	6
●	▲	PTL-38-428	100	4.000 (101.60)	1.900 (48.26)	Asset ID, silver finish	50	41	30	20	10	6
●	▲	PTL-38-435	100	4.000 (101.60)	1.900 (48.26)	Asset ID, silver finish	50	41	30	20	10	6
■	▲	PTL-38-483	100	4.000 (101.60)	1.900 (48.26)	Asset ID for oily, greasy, and textured surfaces	50	41	30	20	10	6
■	▲	PTL-38-486	100	4.000 (101.60)	1.900 (48.26)	Asset ID for oily, greasy, and textured surfaces	50	41	30	20	10	6
■	▲	PTL-38-489	100	4.000 (101.60)	1.900 (48.26)	Asset ID for oily, greasy, and textured surfaces	50	41	30	20	10	6
●	▲	PTL-78-427-AW	250	1.900 (48.26)	1.000 (25.40)	Asset ID for curved surfaces	50	41	30	20	10	6
■	▲	PTL-78-499	250	1.900 (48.26)	1.000 (25.40)	General ID	50	41	30	20	10	6
◆	▲	PTL-80-424	250	0.750 (19.05)	0.900 (22.86)	General ID	50	41	30	20	10	6
◆	▲	PTL-80-488	250	0.750 (19.05)	0.900 (22.86)	Asset ID with print durability	50	41	30	20	10	6
◆	▲	PTL-81-488	750	1.900 (48.26)	0.250 (6.35)	Asset ID with print durability	50	41	30	20	10	6
■	▲	PTL-81-499	750	1.900 (48.26)	0.250 (6.35)	General ID	50	41	30	20	10	6
■	▲	PTL-84-499	500	0.900 (22.86)	0.500 (12.70)	General ID	50	41	30	20	10	6
◆	▲	PTL-97-488	250	0.900 (22.86)	0.900 (22.86)	Asset ID with print durability	50	41	30	20	10	6

\* Any label two inches or larger is rotated on liner.



## ▶ PERMASHIELD™\* LABELS

**Permanent Glossy Polyester (B-422), General Purpose White Paper (B-424), Permanent Metallized Polyester (B-428)**

Surface Suitability	Part Number	Labels Per Roll	Label Dimensions		Overlaminate Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
			A Inch (mm)	B Inch (mm)	C Inch (mm)	D Inch (mm)	2	7	10	2	7	10
●	PTPSL-17-422	500	1.000 (25.40)	0.500 (12.70)	1.250 (31.75)	0.750 (19.05)	24	10	7	5	2	1
◆	PTPSL-17-424	500	1.000 (25.40)	0.500 (12.70)	1.250 (31.75)	0.750 (19.05)	24	10	7	5	2	1
●	PTPSL-17-428	500	1.000 (25.40)	0.500 (12.70)	1.250 (31.75)	0.750 (19.05)	24	10	7	5	2	1
●	PTPSL-20-422	100	2.000 (50.80)	1.000 (25.40)	2.250 (57.15)	1.250 (31.75)	46	19	13	10	5	3
◆	PTPSL-20-424	100	2.000 (50.80)	1.000 (25.40)	2.250 (57.15)	1.250 (31.75)	46	19	13	10	5	3
●	PTPSL-20-428	100	2.000 (50.80)	1.000 (25.40)	2.250 (57.15)	1.250 (31.75)	46	19	13	10	5	3
●	PTPSL-26-422	100	1.250 (31.75)	2.750 (69.85)	1.500 (38.10)	3.000 (76.20)	50	29	19	13	6	4
●	PTPSL-26-428	100	1.250 (31.75)	2.750 (69.85)	1.500 (38.10)	3.000 (76.20)	50	29	19	13	6	4
●	PTPSL-50-422	100	1.650 (41.91)	3.000 (76.20)	1.900 (48.26)	3.250 (82.55)	75	31	21	18	9	6
●	PTPSL-50-428	100	1.650 (41.91)	3.000 (76.20)	1.900 (48.26)	3.250 (82.55)	75	31	21	18	9	6

- ◆ Material suitable for smooth surfaces.
- Material suitable for smooth and textured surfaces.
- Material suitable for smooth, textured and highly textured surfaces.

\* This product is sold in Japan only under the Overlaminate Labels name and not under the PermaShield name.